

BEFORE YOU INSTALL

Each UniClutch is 100% tested and marked with a unique QR code. Scan the code on the base of the clutch to register it before installation. This will unlock exclusive benefits and also give you access to the detailed performance specifications of your unit, including manufacturing data.

UniClutch is a sealed design which has been robotically assembled and 100% tested in our factory guaranteeing performance and quality. A unique QR code is lasered on the bottom of each unit to show manufacturing information and conformity, as well as performance and operation specifications. A UniClutch should **NEVER** be disassembled as this will alter the as tested characteristics and result in an immediate **VOID** of warranty. No service or support can be provided if a UniClutch has been tampered with or disassembled, even after use in a vehicle or upon suspected issues.

This custom installation guide outlines the specifications and installation procedures for the stated vehicle. By using this product, you acknowledge that any deviations from the standard vehicle configuration or failure to follow the installation instructions precisely may impact the validity of the installation and could void the product warranty.

This install guide was acknowledged by the customer on 9 June 2025

YOUR VEHICLE

MAKE: TOYOTA

MODEL: YARIS

YEAR: 02/20-on

VARIANT: 1.6 GR 4WD
(GXPA16) AWD, Petrol, 1.6L,
3Cyl, G16E-GTS, 200kW

REGO: Not provided

VIN: Not provided

VID: 131584

This install guide was
generated on 19 March 2025.

TORQUE



Approximately 150
percent more torque
capacity than OEM.

ACTUATION



Similar actuation effort
to OEM. Pedal release
may be higher.

YOUR NEW UNICLUTCH



Part No.
UC0821200

FITMENT KIT NOTE: Suits OE & UniClutch Ultra Flywheel

YOUR UNICLUTCH FITMENT KIT



Part No.

UCFK08275-A-002 Dowel
Pos E
or UCFK08274-U-01 uses Dowel
Pos C (NAPA US/CA part)
or UCFK08275-A-001 Dowel Pos
E


YOUR FLYWHEEL



Reuse your existing OEM
Spec Flywheel

SPACING REQUIRED

Spacer Height:
14 mm



Bolts supplied must be torqued to 22 ft-
lb /30 Nm.

Apply Loctite® 243 or an equivalent
medium-strength thread locker to the
bolt threads before installation.
For full installation instructions refer to
the installation guide

RELEASE BEARING/CSC GSB968-CSC

SPIGOT BEARING/BUSH

Use OEM style

Unless stated in the Fitment
Kit Notes above, UniClutch
suits OEM service parts. The
above Release Bearing or
CSC and Spigot Bearing or
Bush are references from
Clutch Industries Australia.
Equivalent OEM spec parts
may be used.

THIS INSTALL GUIDE IS ONLY VALID UNTIL 26th March 2025